

:: CA012 Slip Rings

Features

Continuous transmission of signal and/or data under 360° unrestrained rotation Less noise, long life Low torque, smooth rotation Electrical Noise<0.01Ω Small compact construction

Options(On your request)

Number of Circuits Housing material IP class Higher operating speed Cable length Connectors Special cables Salt mist proof Operating temperature Housing can be mounted upside down



CA012 series Slip Rings

Parts#	Circuits(Rings)	Length
CA012-06	6	18.2mm
CA012-12	12	25mm

Specifications							
Working Speed	0~300RPM	Rings	2A/ring,250VDC/VAC				
Housing Material	Plastics	Torque	0.01N.m;+0.01N.m/6rings				
Working life	>50 million revolutions	Contact material	Precious Metal:Gold-Gold				
Electrical noise	<5mOhn	Contact Resistance	<2mOhm				
Dielectric strength	500VDC@50Hz	Lead Wire	UL Teflon® Awg28				
Insulation resistance	1000MΩ@600VDC	Lead Lengths	250mm(12")				
Operating Temp.	-40°C to 80°C	Storage Temp.	-55°C to 85°C				
Bearing	Deep groove ball	Protection	IP51				

Drawings

Ø18

I







CA012-06-C



CA012-06-E

CA012-06-F

Rotor Side Stator Side



CA012-06-G



CA012-12-A

CA012-12-B



Color Code Seq

6 colors for one group, indicated with number code pipe.

Lead wire Color codes									
Rings#	1	2	3	4	5	6			
Color	BLK	RED	YEL	GRN	BLU	WHT			

Typical applications

CCTV pedestal Automatic arm Medical equipments Rotary index table Production line, industry process equipments

Customized on your request

If you don't see what you want in this website, let us know; we may already have it designed or we will modify a design to meet your requirements. In many cases the specifications in the catalog can be changed to include bore size, circuits number, higher current/voltage, flange, lead wire length, shielding, connectors, higher speed, IP68, military grade, higher temperature, mixed with pneumatic/hydraulic capability. Please ask if you don't see exactly what you need as only a small fraction of our Rion slip rings are included in this catalog!

For a detailed outline drawing/3D modal files of a specific model number, or to request a quotation, please contact your local sales representative or send an email to sales@rionsr.com