RIONSR ISO 9001:2008 CERTIFICATION

Focus on 360° Slip Rings & Rotary Union

GOLD-GOLD CONTACT

FOR TB, CA, ET, SDI, WT,PHE SERIES



HFE02 series High Frequency+Electric Hybrid Slip Rings

Features

HFE02 slip rings are 2 channel High Frequency, standard, off-the-shelf. It could support 2 channel High Frequencys(up to 4.5Ghz) transmitting on 360° rotating, The RF rotary joints are needed wherever high-frequency signals have to be transmitted between a fixed platform and second platform in continuous rotation.Such applications includs traditional radar technology for ai traffic control or anti-missile defence,medical engineering, V-sat and Satcom technology as well as TV camera systems or cable drums that allow sensitive cable to be wound.the signal frequency can be DC TO 4.5GHz. HFE02 are often used with electronic sliprings, call optical-electrical hybrid slipring, transmit power and high speed data.

HFE02 series Slip Rings

Online Chat

Options(On your request)

Combine with Power circuits and signal circuits

Parts#	Connector Type
HFE02-SMA	SMA
HFE02-N	N-type

(RF Rotary joints) Specifications			
Max speed	60RPM	Torque	0.1N.m
Frequency	2 channel DC~4.5Ghz	Insertion loss	0.3dB
Insertion loss ripple	0.05dB	VSWR	≤1.3
VSWR ripple	0.05	Start up torque	0.1N.m
Estimated life cycle	100 million	Housing materia	Stainless steel
Working temperature	-40 to 85 °C	Storage temperature	-50 to 85 °C
IP rating	IP 51	Weight	50g

Part#	Fiber Channel	Current(A)	Voltage(VDC/VAC)
HFE02 - (available in stock)			
HFE02-P0610	1	6X10A	440V
HFE02-S06	1	6XSignal(2A)	440V
HFE02-P1210	1	12X10A	440V
HFE02-P0610-S06	1	6X10A+6XSignal(2A)	440V
HFE02-S12	1	12XSignal(2A)	440V
HFE02-P1810	1	18X10A	440V
HFE02-P0610-S12	1	6X10A+12XSignal(2A)	440V
HFE02-S18	1	18XSignal(2A)	440V
HFE02-P2410	1	24X10A	440V
HFE02-P0610-S18	1	6X10A+18XSignal(2A)	440V
HFE02-P1210-S12	1	12X10A+12XSignal(2A)	440V
HFE02-S24	1	24XSignal(5A)	440V
HFE02-S30	1	30XSignal(6A)	440V
HFE02-S36	1	36XSignal(5A)	440V
HFE02-S48	1	48XSignal(5A)	440V

HFE02-S60	1	60XSignal(5A)	440V

Drawings

All parts drawings are different, depends on your request for circuits informations, pls contact us.

Please write circuits num,current,quantity,delivery time or other optional requirements...

Company: Email: Name: Tel:

SEND-TO-US

r>

Typical applications

Industrial machinery-machining centers, rotary index table Heavy equipment turrets, cable reels, test equipments Packaging machines, palletizing machines, magnetic clutch, process equipment Rotary sensors, emergency lighting, robotics Exhibit/display equipment, medical equipment

Customized on your request

If you don't see what you want in this website,let us know; we may already have it designed or we will modify a design to meet your requirements. In many cases the specifications in the catalog can be changed to include bore size, circuits number, higher current/voltage,flange, lead wire length,shielding,connectors,higher speed,IP68,military grade,higher temperature, mixed with pneumatic/hydraulic capability. Please ask if you don't see exactly what you need as only a small fraction of our Rion slip rings are included in this catalog!

For a detailed outline drawing/3D modal files of a specific model number, or to request a quotation, please contact your local sales representative or send an email to sales@rionsr.com